


SPANNSCHLOSS MIT ÖSE, VERPRESST\_TURNBUCKLE WITH EYE SWAGED



Artikelnummer Part number	a	b	ø d1	ø d2	ø Seil ø rope	Spannweg Adjustment	kN
889-0200 <a href="#">dwg</a>	M5	193	5	5,5	2	+26   -43	2,9
889-0300 <a href="#">dwg</a>	M6	220	6	6,5	3	+28   -50	6,7
889-0400 <a href="#">dwg</a>	M6	220	7	6,5	4	+28   -50	11,9
889-0401 <a href="#">dwg</a>	M8	248	8	8,5	4	+34   -50	11,9
889-0500 <a href="#">dwg</a>	M8	254	8	8,5	5	+34   -50	18,5
889-0600 <a href="#">dwg</a>	M10	288	10	10,5	6	+30   -50	26,7
889-0800 <a href="#">dwg</a>	M12	368	13	13	8	+46   -70	44,5
889-1000 <a href="#">dwg</a>	M16	490	18	14,5	10	+48   -90	69,4
889-1200 <a href="#">dwg</a>	M20	570	20	19,5	12	+60   -105	93,6

Werkstoff 1.4401 | kN = Bruchkraft\_Material AISI 316 | kN = breaking load

ALLE ANGABEN IN MILLIMETERN\_ALL DIMENSIONS IN MILLIMETRES

